


ERGOTIG 26


T I G R A N G E

TECHNICAL DATA


Voltage class	L
Inert gas	Argon
Duty cycle 35% DC	180
Duty cycle 35% AC	150
Electrodes Ø mm	0.5 ÷ 4
Cooling	Air cooled




	SINTIG 26	SINTIG 26 FX	m
	SK 1401	SL 1401	4
	SK 1801	SL 1801	8
FITTING M12 x 1	SK 1402	SL 1402	4
FITTING 3/8 G	SK 1802	SL 1802	8



	DUALTIG 26	DUALTIG 26 FX	m
	SK 2401	SL 2401	4
	SK 2801	SL 2801	8
FITTING M12 x 1			




	FRANTIG 26	FRANTIG 26 FX	m
	SK 3401	SL 3401	4
	SK 3801	SL 3801	8
FITTING M12 x 1			



	TIG 26 V	FREE 26	m
	SM 4401	SK 4402	4
	SM 4801	SK 4802	8
FITTING M12 x 1			
FITTING 3/8 G			

Additional KIT	Ø
TT 0103	1.6
TT 0104	2.4
TT 0105	3.2

	AUTOTIG 26	m
	SN 4401	4
	SN 4801	8
FITTING M12 x 1		



DECLARATION OF CONFORMITY

The undersigned company Trafimet - Via del Lavoro, 8 - 36023 Castegnero (VI) - Italy - declares that the product identified and described on this page complies with standard EN 60974-7 in accordance with the requirements contemplated by directive EEC 73/23 low voltage.



EN 60974-7

trafimet®

your welding partner

ERGOTIG 26

T I G R A N G E

